



TAURUS TE 85

Agriculture

The smart choice
for all your tractors up to 150 HP

NEW

New range

- Service life - durability
- High Traction
- Road comfort and self cleaning

Section: From 11.2 to 18.4 inches
(280 to 460 mm)

Rim diameter: From 24 to 38 inches

Cross-ply tyre



Leading the field!



TAURUS

TAURUS TE 85 Range



∅ (inches)	CAI	Tyre size	Ply Rating (PR)	Load & Speed index	Type TL/TT	Recommended rim (permitted rims)	Tube size	Section width (mm)	Overall diameter (mm)	Loaded radius (mm)	Rolling circumference (mm)
24	191709	11.2-24	8 PR	116 A6/112 A8	TT	W10 (W9)	11.2/12.4-24	296	1 105	499	3 286
	158886	12.4-24	8 PR	120 A6/116 A8	TT	W11 (W9-W10)	11.2/12.4-24	327	1 160	521	3 445
28	570308	11.2-28*	8 PR	118 A6/114 A8	TT	W10 (W9)	11.2-28	296	1 205	549	3 591
	146195	12.4-28	8 PR	123 A6/119 A8	TT	W11 (W9-W10)	12.4-28	327	1 260	571	3 750
	954400	13.6-28	8 PR	125 A6/121 A8	TT	W12 (W11)	13.6-28	359	1 310	590	3 894
	127572	14.9-28	8 PR	130 A6/126 A8	TT	W13 (W11-W12)	14.9-28	393	1 365	611	4 052
	639300	16.9-28	10 PR	139 A6/135 A8	TT	W15 (W14L)	16.9-28	446	1 435	637	4 251
30	908544	14.9-30	8 PR	131 A6/127 A8	TT	W13 (W11-W12)	14.9-30	393	1 415	636	4 202
	632943	16.9-30	12 PR	143 A6/139 A8	TT	W15L (W14L)	16.9-30	446	1 485	662	4 403
	658394	18.4-30	10 PR	145 A6/141 A8	TT	W16L (W15L)	18.4-30	485	1 550	687	4 590
34	463653	18.4-34	14 PR	154 A6/150 A8	TT	W16L (W15L)	18.4-34	485	1 650	737	4 895
36	009883	13.6-36*	8 PR	129 A6/125 A8	TT	W12 (W11)	13.6-36	359	1 515	692	4 518
38	941362	14.00-38*	8 PR	131 A6/127 A8	TT	W12 (W11)	13.6-38	369	1 565	715	4 668
	310424	15.5-38*	12 PR	141 A6/137 A8	TT	W14L	15.5-38	411	1 630	741	4 855

Load per tyre in kg according to speed				Pressure		75% internal volume
10 km/h	20 km/h	30 km/h	40 km/h	bar	PSI	
1 415	1 210	1 010	910	1.5	22	92
1 525	1 310	1 090	980	1.8	26	
1 640	1 405	1 170	1 050	2.1	30	
1 750	1 500	1 250	1 125	2.4	35	
1 615	1 385	1 155	1 040	1.5	22	116
1 702	1 460	1 215	1 095	1.7	25	
1 830	1 570	1 310	1 180	2.0	29	
1 960	1 680	1 400	1 260	2.3	33	
1 495	1 280	1 070	960	1.5	22	103
1 610	1 380	1 150	1 040	1.8	26	
1 730	1 485	1 235	1 115	2.1	30	
1 850	1 585	1 320	1 190	2.4	35	
1 770	1 520	1 270	1 140	1.5	22	130
1 870	1 610	1 340	1 200	1.7	25	
2 020	1 735	1 445	1 300	2.0	29	
2 170	1 860	1 550	1 395	2.3	33	
1 820	1 565	1 300	1 170	1.2	17	160
2 005	1 720	1 435	1 290	1.5	22	
2 130	1 825	1 520	1 370	1.7	25	
2 310	1 980	1 650	1 485	2.0	29	
2 100	1 800	1 500	1 350	1.0	15	198
2 240	1 920	1 600	1 440	1.2	17	
2 450	2 100	1 750	1 575	1.5	22	
2 660	2 280	1 900	1 710	1.8	26	
2 700	2 310	1 930	1 735	1.2	17	265
2 960	2 540	2 115	1 900	1.5	22	
3 140	2 690	2 240	2 020	1.7	25	
3 400	2 915	2 430	2 185	2.0	29	
2 100	1 800	1 500	1 350	1.0	15	207
2 260	1 935	1 615	1 450	1.2	17	
2 495	2 140	1 780	1 605	1.5	22	
2 730	2 340	1 950	1 755	1.8	26	
3 150	2 700	2 250	2 025	1.5	22	277
3 315	2 840	2 370	2 130	1.7	25	
3 565	3 055	2 550	2 295	2.0	29	
3 815	3 270	2 725	2 455	2.3	33	
3 135	2 690	2 240	2 015	1.0	15	338
3 366	2 888	2 405	2 165	1.2	17	
3 715	3 185	2 650	2 390	1.5	22	
4 060	3 480	2 900	2 610	1.8	26	
3 720	3 190	2 660	2 390	1.2	17	368
4 160	3 560	2 970	2 670	1.6	23	
4 595	3 940	3 280	2 955	2.0	29	
5 250	4 500	3 750	3 375	2.6	38	
2 090	1 790	1 490	1 340	1.2	17	192
2 275	1 950	1 625	1 465	1.5	22	
2 400	2 060	1 715	1 545	1.7	25	
2 590	2 220	1 850	1 665	2.0	29	
2 170	1 860	1 550	1 395	1.2	17	214
2 380	2 040	1 700	1 530	1.5	22	
2 520	2 160	1 800	1 620	1.7	25	
2 730	2 340	1 950	1 755	2.0	29	
2 380	2 040	1 700	1 530	1.4	20	269
2 800	2 400	2 000	1 800	1.8	26	
3 220	2 760	2 300	2 070	2.3	33	
3 605	3 090	2 575	2 300	2.8	41	

* under preparation